

MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

1. IDENTIFICATION OF THE MATERIAL AND THE MANUFACTURER

Product Name MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Ink 500 ml.

Statement of Considered a Hazardous Substance according to the criteria of the New Zealand

Hazard Nature Hazardous Substances, New Organisms legislation.

Classified as a Dangerous Good for transport purposes.

Proper Shipping

Name

AEROSOLS

Supplier Name Arandee Ltd

Address 108 Rockfield Road, Penrose, Auckland 1061, New Zealand

Telephone +64 (9) 579 5139 **Fax** +64 (9) 579 7628

Emergency National Poisons Centre -24 hours Australia 13 11 26

New Zealand 0800 POISON

0800 764 766

E-mail <u>sales@arandee.co.nz</u>

Web Site http://www.arandee.co.nz

Synonym(s) MAC SprayMark Upside Down; MAC Spray Inverted

Use(s) A rapid drying, block-free, permanent spray for contractor survey & horticultural Layout, use

when permanent, fade free marks are required. Effective on most surfaces; in all weather conditions. Low mammalian toxicity, an important consideration for the safety of staff

involved in frequent use.

Approval(s) N/A

2. HAZARDS IDENTIFICATION

AEROSOL - CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA IN THE HS (MIN DEG OF HAZ) REGS 2001 CLASSIFIED AS A DANGEROUS GOOD, UNDER ADG AND NZS 5433

UN Number	1950		Dangerous Goods Risks		
DG Class	2.1.2A	2Y	Contains gas under pressure; may explode if heated Contains refrigerated gas; may cause cryogenic burns or injury.		
HAZARD STATEMENT		223	Flammable aerosols		
PRECAUTIONARY		P210	Keep away from heat/sparks/open flame/hot surfaces		
STATEMENTS		P211	Do not spray on an open flame, or other ignition source.		
		P251	Pressurized container. Do not pierce or burn even after use		
		P403	Store in a well ventilated place.		
		P410	Protect from direct sunlight		
		P412	Do not expose to temperatures exceeding 50°C/122°F		

MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

3. HAZARDS IDENTIFICATION COMPOSITION OF INGREDIENTS

Ingredient	Formula	Concentration	CAS Number
ACETONE	C₃H ₆ O	30 - 60%	67-64-1
PROPYLENE GLYCOL MONOMETHYL ETHER – ALPHA ISOMER	C ₃ H ₈ O ₂	1 - 10%	107-98-2
DIMETHYL ETHER	C ₂ H ₆ O	10 - 30%	115-10-6
HYDROCARBON PROPELLANT	C₃H ₈	10 - 30%	68476-85-7

4. FIRST AID MEASURES

Eye Hold eyelids apart and flush continuously with water. Continue until advised to stop by the

Poisons Information Centre, a doctor, or for at least 15 minutes. Keep patient calm.

Inhalation Leave area of exposure immediately. If irritation persists, seek medical attention.

Skin Gently flush affected areas with water. Seek medical attention, if irritation persists.

Ingestion For advice, contact a Poisons Information Centre on 0800 764 766 (0800 POISON) or +64 9 579

5139 (New Zealand) or a doctor. If swallowed, DO NOT induce vomiting, as ingestion is considered

unlikely, due to the product form.

Advice to Doctor Treat symptomatically.

First Aid Facilities Eye wash facilities should be provided.

5. FIRE FIGHTING MEASURES

Flammability Highly flammable. Vapours may form explosive mixtures with air. May evolve toxic gases (carbon

oxides, hydrocarbons) when heated to decomposition temperatures. When handling a significant spillage, eliminate all ignition sources, including cigarettes, open flames, spark producing switches, heaters, naked lights, mobile phones, etc. Aerosol cans may explode when heated

above 50 ºC.

Fire and Will burn if involved in a fire. Evacuate area and contact emergency services. Toxic gases may

evolve, when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment, including Self Contained Breathing Apparatus (SCBA), when combating fire. Use water

fog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide foam, or water fog. Prevent contamination of drains or waterways;

absorb runoff with sand or similar.

HazChem 2Y NFPA Ratings: Health: 1 Flammability 4 Reactivity: 1

6. ACCIDENTAL RELEASE MEASURES

Explosion

SAFETY DATA SHEET



MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

Spillage If large quantities of cans are punctured (bulk), clear area of all unprotected personnel and

ventilate area. Wear splash-proof goggles, leather gloves, coveralls, and boots. Where inhalation risks exist, wear a Type A-Class P1 (Organic vapour and Particulate) respirator. Collect cans and allow to discharge outdoors. Absorb any residues with sand or similar and place in clean containers for disposal. DO NOT wash away into sewer.

7. HANDLING AND STORAGE

Handling Use safe work practices to avoid eye or skin contact and inhalation. Observe good personal

hygiene, including washing hands before eating. Keep out of the reach of children.

DO NOT puncture aerosol cans or incinerate, even when empty.

Storage Store in a cool, dry well ventilated area, well away from oxidising agents, acids, alkalis, direct

sunlight, heat or ignition sources, or foodstuffs. Ensure containers are adequately labelled, protected from physical damage, and sealed when not in use. Check regularly for leaks or spills.

Large storage areas should have appropriate fire protection.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation DO NOT directly inhale concentrated vapours. Use in well-ventilated areas. Mechanical extraction

ventilation is recommended for poorly ventilated area. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the

recommended exposure standard.

Exposure Refer to OSHA Standard 29CFR1910.134.

Standards
LIQUIFIED PEROLEUM GAS (LPG) (68476-85-7)

ES-STEL: 400ppm (1800 mg/m³)

Personal No personal protective equipment is required, normally. When an inhalation risk exist wear a

Protection Type A-Class P1 (Organic vapour and Particulate) Respirator. With prolonged use, wear PVC or

Equipment rubber gloves and splash-proof goggles or safety glasses.





100 %

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance COLOURLESS AEROSOL Solubility (water) NONE

GAS

Odour SLIGHT, ETHEREAL-LIKE Specific Gravity 0.83 - 0.85

ODOUR

NOT AVAILABLE

% Volatiles

Vapour Pressure65-75 psi@30°CFlammabilityHIGHLY FLAMMABLEVapour Density> 4 (Air = 1)Flash Point< 0 °C (Propellant)</th>

Melting Point NOT AVAILABLE Upper Explosion Limit NOT AVAILABLE

рН

SAFETY DATA SHEET



MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

 Boiling Point
 NOT AVAILABLE
 Lower Explosion Limit
 NOT AVAILABLE

 Evaporation Rate
 FAST
 Auto-ignition Temperature
 NOT AVAILABLE

10. STABILITY AND REACTIVITY

Stability Stable at normal temperatures and pressures. Store below 40°C, away from sources of ignition

and incompatible substances such as, Alkali and alkaline earth minerals, aluminium powder,

magnesium and beryllium, strong oxidisers and acids.

Decomposition

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition

Products temperatures.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary General population. The exposure of the general population is expected to be low and is not likely

to present a hazard when it is used as recommended.

Occupational exposure. With reasonable work practices, hygiene measures and

Safety precautions, is unlikely to be an occupational hazard.

Asphyxiant narcotic. This product may only present a hazard with direct eye contact, prolonged

and repeated skin contact or with vapour/gas inhalation at high levels.

Eye Severe irritant. Contact may result in lacrimation, pain, redness, and conjunctivitis. Prolonged

contact may result in corneal burns, with possible permanent damage.

Inhalation Low to moderate Irritant, narcotic, asphyxiant. Over exposure may result in upper respiratory

tract irritation, nausea, and headache. At high levels; dizziness, breathing difficulties, and at very

high levels, anaesthesia, cardiac arrhythmias, pulmonary oedema and unconsciousness.

Skin Low irritant. Prolonged contact may result in irritation, redness, rash, dermatitis, and

sensitisation.

Ingestion Exposure considered unlikely, due to product form as an aerosol. Under normal conditions of use,

ingestion is considered a highly unlikely, exposure route.

Toxicity Data LD50 (Skin): 2500 ug/kg (rat)

LD50 (Ingestion): 1000 mg/kg (mouse)

12. ECOLOGICAL INFORMATION

Environment Environmental effects of the compound are extremely unlikely, due to packaging in the form of an

aerosol. Ensure appropriate measures are taken to prevent this product from entering the

environment through wastewater.

13. DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts, absorb contents with sand or similar and dispose of to an approved landfill

site. DO NOT puncture or incinerate aerosol cans. Contact the manufacturer for additional

information.



MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

Legislation

Dispose of in accordance with relevant, local legislation.

14. TRANSPORT INFORMATION

	Shipping Name	UN No	Packing Group	DG Class	Subsidiary Risk(s)	EPG
Land	Compressed Gas Flammable Aerosol	1950	None Allocated	2.1	None Allocated	2C1
Sea	Compressed Gas Flammable Aerosol	1950	III	2.1	None Allocated	2C1



Shipping Label

REGULATORY INFORMATION **15.**

Poison Schedule

AICS

This product does not contain any CLASS 1 ozone depletors.

This product does not contain any CLASS 2 ozone depletors.

A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

OTHER INFORMATION

Additional Information

ASPHYXIANTS (1): reduce the oxygen concentration by displacement, when present in the atmospheres, in high concentrations. As most simple asphyxiants are odourless, atmospheres deficient in oxygen do not provide adequate sensory warning of danger. Therefore, it is not generally appropriate to recommend an exposure standard for each asphyxiant, but instead warn of the need to maintain oxygen concentrations.

Some asphyxiants may be given an exposure standard, due to their potential for narcotic effects at high concentrations, or an explosion hazard.

Asphyxiants (2)

There is a significant hazard associated with workers entering poorly, ventilated areas (e.g. tanks) where oxygen levels may be deficient. An air supplied breathing apparatus may be required if adequate ventilation is not ensured. Refer to AS/NZS 2865 - Safe Working in a Confined Space.

Respirators

In general, the best practice to avoid exposure is to use engineering controls, such as adequate ventilation, rather than the use of respirators (which should be limited).

If respiratory equipment must be worn, ensure correct respirator selection and training is undertaken. Some respirators may be extremely uncomfortable, when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

SAFETY DATA SHEET



MAC SPRAYMARK UPSIDE DOWN

Aerosol Spray Paint - Inverted Marker

Abbreviations

Mg/m3 - Milligrams per cubic metre

ppm -Parts Per Million

M - moles per litre, a unit of measure of concentration.

pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 - 14,

where 0 is highly acidic and 14 is highly alkaline.

TWA/ES - Time Weighted Average or Exposure Standard.

CAS# - Chemical Abstract Service number - uniquely identifies chemical compounds.

CNS - Central Nervous System NOS - Not Otherwise Specified

IARC - International Agency for Research on Cancer.

Personal Protective Equipment

The recommendations for protective equipment contained within this SDS report are provided as a guide only, when dealing with an abnormal situation. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered, before the final selection of personal protective equipment is made.

Health Effects From Exposure

It should be noted that the effects from excess exposure to this product would depend on several factors, including duration of exposure, quantity involved, effectiveness of control measures used; protective equipment and method of application. Given that, it is impractical to prepare a SDS report, which would encompass all possible scenarios, it is anticipated that users will assess the risks in an emergency and apply appropriate control methods.

Report Status

This report is based upon information provided by ingredient manufacturers, and third party experts. We believe that the information represents the current state of knowledge about safety and handling precautions that are appropriate for this product. Further clarification regarding any aspect of the product should be obtained directly from the Chief Chemist at Arandee Ltd. While Arandee has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy, or completeness. As far as lawfully possible, Arandee accepts no liability for any loss, injury, or damage (including consequential loss) which may be suffered, or incurred by any person, because of their reliance upon the information contained in this Safety Data Sheet.